

# Specifications

I-110XL2

I-110TS2

I-130XL2

I-130TS2

I-155XL2

I-155TS2

	English	Metric	English	Metric	English	Metric	English	Metric	English	Metric	English	Metric
Capacity, heaped	11.3 cu. yd.	8.6 cu. m.	11.3 cu. yd.	8.6 cu. m.	13.3 cu. yd.	10.2 cu.m.	13.3 cu. yd.	10.2 cu.m.	15.5 cu. yd.	11.9 cu. m.	15.5 cu.. yd.	11.9 cu. m.
Capacity, struck	8.2 cu. yd.	6.3 cu. m.	8.2 cu. yd.	6.3 cu. m.	10.2 cu. yd.	7.8 cu.m.	10.2 cu. yd.	7.8 cu.m.	11.9 cu. yd.	9.1 cu. m.	11.9 cu.. yd.	9.1 cu. m.
Width of cut	97.5 in	248 cm.	97.5 in	248 cm.	97.5 in.	248 cm.	97.5 in.	248 cm.	108.5 in.	276 cm.	108.5 in.	246 cm.
Apron clearance	56 in.	142 cm.	56 in.	142 cm.	56 in.	142 cm.	56 in.	142 cm.	62 in.	157 cm.	62 in.	157 cm.
Overall width	112.5 in.	286 cm.	112.5 in.	286 cm.	112.5 in.	286 cm.	112.5 in.	286 cm.	120 in.	305 cm.	120 in.	305 cm.
Depth of cut	8 in.	20.3 cm.	8 in.	20.3 cm.	8 in.	20 cm.	8 in.	20.3 cm.	8 in.	20.3 cm.	8 in.	20.3 cm.
Depth of spread	0-15 in.	0-38 cm.	0-15 in.	0-38 cm.	0-15 in.	0-38 cm.	0-15 in.	0-38 cm.	0-16.5 in.	0-42 cm.	0-16.5 in.	0-42 cm.
Ground clearance @ blade	15 in.	38 cm.	15 in. std. (18 in. opt'l)	38 cm.	15 in.	38 cm.	15 in std. (18 in. opt'l)	38 cm. (46 cm. opt'l)	16.5 in.	42 cm.	16.5 in.	42 cm.
Overall height, raised	74 in.	188 cm.	74 in.	188 cm.	85 in.	216 cm.	85 in.	216 cm.	102 in.	259 cm.	102 in.	259.1 cm.
Overall Length	339 in.	861 cm.	324 in.	823 cm.	339 in.	861 cm.	324 in.	823 cm.	360 in.	914 cm.	365 in.	927 cm.
Pushgate cylinder (1), std	4 in. x 54 in.	10.2 cm. x 137 cm.	4 in. x 54 in.		4.5 in. x 54 in.	11.4 cm. x 137.2 cm.	4.5 in. x 54 in.	11.4 cm. x 137.2 cm.	5 in x 60 in.	12.7 cm. x 152.4 cm.	5 in. x 60 in.	12.7 cm. x 152.4 cm.
Pushgate cylinder (1) opt'l	4.5 in. x 54 in.	11.4 cm. x 137 cm.	4.5 in. x 54 in.	11.4 cm. x 137 cm.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Apron cylinders (2)	4 in. x 13 in.	10.2 cm. x 33 cm.	4 in. x 13 in.	10.2 cm. x 33 cm.	4 in. x 13 in.	10.2 cm. x 33 cm.	4 in. x 13 in.	10.2 cm. x 33 cm.	4 in. x 13 in.	10.2 cm. x 33 cm.	4 in. x 13 in.	10.2 cm. x 33 cm.
Lift cylinders (2), std.	4 in. x 16 in.	10.2 cm x 41 cm.	4 in. x 16 in. Trunion	10.2 cm x 41 cm.	5 in. x 16 in.	12.7 cm x 41 cm.	5 in. x 16 in. Trunion	12.7 cm x 41 cm.	5 in.. x 20 in.	12.7 cm. x 50.8 cm.	5 in. x 20 in. Trunion	12.7 cm.x 50.8 cm.
Lift cylinders (2), opt'l	5 in. x 16 in.	12.7 cm x 41 cm.	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Sequencing valve	Standard		Standard		Standard		Standard		Standard		Standard	
Separate hyd. circuits for apron & push-off	Optional		Optional		Optional		Optional		Optional		Optional	
Tire size, rear, standard	18.4 x 26 - 10 ply		20.5 x 25 - 12 ply		18.4 x 26 - 12 ply		20.5 x 25 - 12 ply		29.5 x 25 - 28 ply OTR		29.5 x 25 - 28 ply OTR	
Tire size, rear, optional	20.5 x 25 - 12 ply		20.5 x 25 - 16 ply		20.5 x 25 - 12 ply							
Tire size, front	16.5 x 16.1 -10 ply ANS				21.5 x 16.1-10 ply				20.5 x 25 - 12 ply		N/A	
Weight Standard	11,900 lbs.	5,398 Kg.	13,200 lbs.	5,987 Kg.	12,900 lbs.	5,851 Kg.	13,500 lbs.	5,851 Kg.	20,500 lbs.	9,299 Kg.	19,300 lbs.	8,754Kg.
Weight, with optional rear tire	13.400 lbs.	6,078 Kg.	12,900 lbs.	6,123 Kg.	13,300 lbs.	6,078 Kg.	14,000 lbs.	6,078 Kg.	21,650 lbs.	9,820 Kg.		

For more information on the Industrial Series as well as all of the models Ashland offers please visit our website

[www.ashlandind.com](http://www.ashlandind.com)